

LLT100 Laser level transmitter

The new standard in industrial laser level transmitters

Measurement made easy



Customer benefits

The LLT100 is specifically made for industrial applications and harsh environments. It provides continuous, non-contact level measurement capabilities for process automation and inventory management in industries such as mining, aggregates, oil & gas, chemicals, food & beverages, power, pulp & paper, pharma, and water & waste water.

Optimize process or inventory management

- Precise measurement of any solid or liquid
- Independent of material properties

Low cost of ownership

- Fast and flexible installation
- No maintenance
- Single product configuration works for many applications

Main features

ABB brings laser level transmitters to the next level of noncontact measurements by packaging laser ranging technology with the required features for industrial applications. Using a pulsed laser for performing time of flight measurement, LLT100 provides accurate distance measurements while being powered from the 4 to 20 mA loop. Available in aluminum or stainless steel body, it comes with a variety of process interfaces. It can meet the demands of hazardous area locations, high pressure and high temperature applications.

Convenient

- Easy setup function
- Orientable embedded graphical user interface
- 2-wire powered and HART 7 communication

Reliable

- Dust and fog penetration capabilities
- Accurate measurement at short and long distances
- Explosion-proof class 1, division 1 (zone 1)

LLT100

Laser level transmitter

Product configurations

Base model

Ideal for measuring the level of solids at up to 100 m (328 ft.) and liquids at up to 30 m (98 ft.) when the process is at normal pressures. Affordable, powerful level transmitter for a wide range of applications, even in hazardous areas.

Range	0.5 m to 100 m (2 ft. to 330 ft.)
Process fitting	ASME class 150, NPS 2 in. DN 50 PN 16 flat face
Operating temperature	-40°C to +60°C (-40°F to +140°F)
Process pressure	-1 to +2 bar (29 psi)
Accuracy	±2 cm (0.8 in.)



Hygienic model

Ideal for food and beverage or pharmaceutical applications. Model fitted with a 4 in. triclover clamp interface with hygienic certifications. As all models, available with aluminum or stainless steel enclosure.

Range	0.5 m to 100 m (2 ft. to 330 ft.)
Process fitting	4 in. triclover clamp
Operating temperature	-40°C to +60°C (-40°F to +140°F)
Process pressure	-1 bar to +1 bar (15 psi)
Accuracy	±2 cm (0.8 in.)



High pressure models

Ideal for high-pressure applications. Same performance as the base model, but fitted with a choice of pressure rated flanges. As all models, is certified for use in hazardous area zone 1, and laser beam can be sent safely into zone 0.

Range	0.5 m to 100 m (2 ft. to 330 ft.)
Process fitting	ASME class 150/300, NPS 2 in. DN 50 PN 16/40 raised face
Process temperature	-40°C to +60°C (-40°F to +140°F)
Process pressure	-1 to +50 bar (720 psi)
Accuracy	±2 cm (0.8 in.)



Accessories

Configure the transmitter to a wide variety of applications.

- Dust tube
- Purge ring for dust tube
- Cooling tube (increases maximum process temperature to 280°C (535°F))
- Heated window (requires 4-wire power)
- Through-The-Glass HMI
- Flange adapters
- Alignment laser pointer
- External relays
- Rotating bracket, swivel flange

LLT100

Laser level transmitter

Functions



Advantages / New features

Laser transmitter measures any solid or liquid, from close to long range. A single instrument meets a wide variety of demands.

LLT100 can be used in challenging hazardous areas, in the presence of potentially explosive dust or gases. It can be used in class 1 / division 1 (zone 1) environments. For zoned environments, the LLT100 configured with fused glass process flanges is approved for forming the barrier between zone 1 and zone 0 and sending its laser beam into zone 0.

For dusty applications, the dust tube prevents dust deposition on the window, removing the need for preventive maintenance. For very high dust level, a purge ring can be added to the dust tube to provide an air flow to enhance the dust protection.


High temperature applications are made possible by the addition of a cooling tube. Cooling tubes with different process interfaces and different pressure ratings are available.

Solid application

A typical LLT100 application is to measure the level of solid materials in silos or tanks. They can be found in various industries such as mining, aggregates, chemicals, food and beverages, power, pulp and paper, pharma.

The high sensitivity of the LLT100 allows level measurement in tall vessels. Its narrow laser beam can be precisely aimed around obstacles, and instrument installation is very flexible, as the transmitter can be placed close to the wall or be aimed at an angle inside the vessel. Finally, material build-up on vessel sides has no effect on the measurement, as the narrow beam (beam angle <math><0.3</math> degrees) does not interact with the vessel sides.

The new LLT100 sets the new standard for industrial laser level measurement.




Liquid application

Liquid measurement represents a large portion of level applications. LLT100 can detect any liquid, even transparent liquids.

The LLT100 comes with the heated window option to prevent condensation on its optics.

In liquid application, the laser beam must be as perpendicular as possible to the liquid surface. Alignment of the beam should be within ± 5 degrees from vertical. To help in performing the alignment of the beam, the swivel flange accessory is very convenient as it provides a simple and efficient way to precisely align the laser beam.

For high pressure applications, the LLT100 comes with a variety of process flanges, rated at pressure up to 50 bar (725 psi).




LLT100

Laser level transmitter

Mixer / Obstruction

Another challenge in the field of level measurement is the reliable measurement in the presence of obstructions or mixing blades.

The narrow beam of the LLT100 allows to install the device at almost any place at the top of the vessel. Coupled with the fact that the laser beam is very narrow (<0.3 degrees), it can easily be positioned between the vessel wall and the edge of the mixer, providing reliable measurements. When it is not possible to avoid the mixer blades, the LLT100 has advanced processing functions that can still perform the measurement reliably by efficiently tracking the real level when the mixer crosses the path of the laser beam.




Positioning

Another application for the LLT100 is to measure the position of wagons, tripper cars or other moving objects in order to position them accurately.

A tripper car being positioned in the wrong place when it unloads its cargo causes wasted time, damage, and lost time. Similarly, the LLT100 can be used to prevent collisions by moving cranes and other machinery.

The LLT100 can provide accurate position measurement at distances up to 200 m (660 ft) with the added use of a reflector.



Specification

Measurement

Range

- 0.5 m to 30 m (2 ft. to 100 ft.) for liquids
- 0.5 m to 100 m (2 ft. to 330 ft.) for solids
- 0.5 m to 200 m (2 ft. to 660 ft.) for positioning applications with reflective target

Resolution

- 5 mm (0.2 in.)

Accuracy

- ±20 mm (0.8 in.)

Measuring beam

- Laser wave length: 905 nm, eye safe, Class 1

Laser beam divergence

- < 0.3°

Environmental conditions

Operating temperature

- 40°C to +60°C (-40°F to +140°F)

Storage temperature

- 40°C to +85°C (-40°F to +185°F)

Survival temperature

- 40°C to +80°C (-40°F to +175°F)

Process pressure

- Base model: -1 to +2 bar (29 psi)
- Hygienic model: -1 to +1 bar (15 psi)
- Pressure-rated model: -1 to +49.6 bar (719 psi), depending on flange

Output

Analog

- 4 to 20 mA, NAMUR compliant

Digital

- HART 7 (multi-variable output)

Communication

- Local HMI, EDD/DTM, handheld

Power supply

Powered from the loop

- 4 to 20 mA, 15.5 to 42 V DC (if using HART minimum input voltage is 21 V DC)

Heated lens option

- 24 V DC (3W)

Mechanical

Enclosure material

- Powder coated aluminum (standard), 316L stainless steel (option)

Dimensions

- Universal - flat flange W 247 x H 215 x D 165 mm (9.7 x 8.5 x 6.5 in.)
- Class 150 - raised flange W 240 x H 242 x D 154 mm (9.5 x 9.5 x 6.1 in.)
- Class 300 - raised flange W 247 x H 242 x D 165 mm (9.7 x 9.5 x 6.5 in.)
- DIN PN 16 - raised flange W 247 x H 242 x D 165 mm (9.7 x 9.5 x 6.5 in.)
- DIN PN 40 - raised flange W 247 x H 242 x D 165 mm (9.7 x 9.5 x 6.5 in.)
- Hygienic flange W 223 x H 215 x D 137 mm (8.8 x 8.5 x 5.4 in.)

Weight of standard model

- Aluminum enclosure with universal aluminum flange: 3.7 kg (8.2 lb)
- 316L stainless steel enclosure with universal stainless steel flange: 8.6 kg (19.0 lb)

Weight of pressure rated model

- Aluminum enclosure: 6.7 to 7.2 kg (14.8 to 15.9 lb) depending on flange
- 316L stainless steel enclosure: 10.0 to 10.5 kg (22.1 to 23.2 lb) depending on flange

Weight of hygienic model

- Aluminum enclosure: 5.8 kg (12.8 lb)
- 316L stainless steel enclosure: 9.1 kg (20.1 lb)

Protection class

- IP66 / IP 67 / type 4X (for all versions except flange H which is IP66 / type 4X)

Process fitting

- Flange (ASME 2 in., DN50), hygienic fitting / tri-clamp 4 in. (ISO2852)

Wetted parts

- Aluminum, cemented borosilicate window (base model)
- 316L SST, cemented borosilicate window (base model, hygienic model)
- 316L SST, fused borosilicate window (high pressure models)

LLT100

Laser level transmitter

Operation

Display

Integrated 128 x 64 pixels LCD display with TTG (Through-The-Glass) interface

Software features

Volume computation, damping, filtering, thresholds/alarms, user-defined display (with HMI)

Optical

Total optical aperture

50 mm (2 in.)

Standard window material

Tempered borosilicate cemented glass

Pressure rated window material

Borosilicate fused glass

Lens impact resistance

Impact tested at 4 joules

Beam divergence

$\Delta < 0.3^\circ$

Beam spot width

Distance	1 m	3 m	5 m	10 m	20 m	30 m	50 m	100 m	150 m
	(3 ft.)	(10 ft.)	(16 ft.)	(33 ft.)	(66 ft.)	(98 ft.)	(164 ft.)	(328 ft.)	(492 ft.)

approx. 0.7 cm 2.0 cm 3.3 cm 6.6 cm 13.5 cm 20 cm 34 cm 69 cm 108 cm

spot (0.3 in.) (0.8 in.) (1.3 in.) (2.6 in.) (5.3 in.) (7.9 in.) (13.4 in.) (27.2 in.) (42.5 in.)

width

Beam direction

$90^\circ \pm 5^\circ$ from mounting flange for measurements of liquids

Laser

Measuring laser

905 nm near infrared pulsed semiconductor laser

7.1 μ W average power output

45 W peak power output

Measuring laser life expectancy

25 years typical MTBF

Measuring laser safety

Always on IEC60825-1 Ed 2, 2007

A class 1 laser is safe for all conditions of use.

Approvals

<p>CE</p> 	<p>ATEX Directive 2014/34/EU Electromagnetic compatibility Directive (EMC) 2014/30/EU Low Voltage Directive (LVD) 2014/35/EU Restriction of Hazardous Substances Directive ROHS II 2011/65/EU</p>	<p>Applied standards: EN 61326-1:2013, EN/IEC 60529, EN/IEC 61010-1:2010, EN/IEC 60825-1</p>
<p>ATEX, IECEx</p> 	<p>ATEX: FM16ATEX0032X, IECEx FMG 16.0023X For flanges A and B: II 2 (1) G Ex db [op is T6 Ga] IIC T6...T5 Gb -50°C ≤ Ta ≤ +75°C...+85°C II 2 (1) D Ex tb [op is Da] IIIC T85°C...T100°C Db -50°C ≤ Ta ≤ +75°C...+85°C - IP66/IP67 Ex db [op is T6 Ga] IIC T6...T5 Gb -50°C ≤ Ta ≤ +75°C...+85°C Ex tb [op is Da] IIIC T85°C...T100°C Db -50°C ≤ Ta ≤ +75°C...+85°C - IP66/IP67 For flanges C, D, F, and G: II 1/2 (1) G Ex db [op is T6 Ga] IIC T6...T5 Ga/Gb -50°C ≤ Ta ≤ +75°C...+85°C II 2 (1) D Ex tb [op is Da] IIIC T85°C...T100°C Db -50°C ≤ Ta ≤ +75°C...+85°C - IP66/IP67 Ex db [op is T6 Ga] IIC T6...T5 Ga/Gb -50°C ≤ Ta ≤ +75°C...+85°C Ex tb [op is Da] IIIC T85°C...T100°C Db -50°C ≤ Ta ≤ +75°C...+85°C - IP66/IP67</p>	<p>EN/IEC 60079-0, EN/IEC 60079-1, EN/IEC 60079-26, EN/IEC 60079-28, EN/IEC 60079-31, EN/IEC 60529</p>
<p>FM</p> 	<p>FM16US0106X, FM16CA0060X US & CANADA, ENCL. Type 4X, IP66/IP67, "Seal not required" - "DUAL SEAL" For flanges A, B, C, D, F, and G and only for housings AI and SI: US: Class I, Division 1, Groups A, B, C, D T5 -50°C ≤ Ta ≤ 85°C US: Class I, Division 1, Groups A, B, C, D T6 -50°C ≤ Ta ≤ 75°C CAN: Class I, Division 1, Groups B, C, D T5 -50°C ≤ Ta ≤ 85°C CAN: Class I, Division 1, Groups B, C, D T6 -50°C ≤ Ta ≤ 75°C Class II/III, Division 1, Groups E, F, G T5 -50°C ≤ Ta ≤ 85°C Class II/III, Division 1, Groups E, F, G T6 -50°C ≤ Ta ≤ 75°C For flanges A, B, C, D, F, and G and only for housings AM and SM: US only: Class I, Division 1, Groups A, B, C, D T5 -50°C ≤ Ta ≤ 85°C US only: Class I, Division 1, Groups A, B, C, D T6 -50°C ≤ Ta ≤ 75°C US only: Class II/III, Division 1, Groups E, F, G T5 -50°C ≤ Ta ≤ 85°C US only: Class II/III, Division 1, Groups E, F, G T6 -50°C ≤ Ta ≤ 75°C For flanges A and B: Class I, Zone 1, AEx/Ex db [op is T6 Ga] IIC T6...T5 Gb -50°C ≤ Ta ≤ +75°C...+85°C Zone 21, AEx/Ex tb [op is Da] IIIC T85°C...T100°C Db -50°C ≤ Ta ≤ +75°C...+85°C For flanges C, D, F, and G: Class I, Zone 0/1, AEx/Ex db [op is T6 Ga] IIC T6...T5 Ga/Gb -50°C ≤ Ta ≤ +75°C...+85°C Zone 21, AEx/Ex tb [op is Da] IIIC T85°C...T100°C Db -50°C ≤ Ta ≤ +75°C...+85°C</p>	<p>FM Class 3600:2011, FM Class 3615:2006, FM Class 3616:2011, FM Class 3810:2005, ANSI/ISA 61010-1:2012, ANSI/ISA 60079-0:2013, ANSI/UL 60079-1:2015, ANSI/ISA 60079-26: 2011, ANSI/ISA 60079-28:2013, ANSI/ISA 60079-31:2015, ANSI/ISA 12.27.01:2011, ANSI/NEMA 250:2014, ANSI/IEC 60529:2004 CSA-C22.2 No. 0.4:2013, CSA-C22.2 No. 0.5:2012, CSA-C22.2 No. 25:2014, CSA-C22.2 No. 30:2012, CSA-C22.2 No. 94:2011, CAN/CSA-C22.2 No. 60079-0:2015, CAN/CSA-C22.2 No. 60079-1:2011, CAN/CSA-C22.2 No. 60079-31:2015, CSA-C22.2 No. 60529:2015, CAN/CSA-C22.2 No. 61010-1:2012</p>
<p>CSA</p> 	<p>CLASS - C363186 - ELECTRICAL EQUIPMENT FOR MEASUREMENT USE - Certified to US Standard CLASS - C363106 - ELECTRICAL MEASUREMENT AND TEST EQUIPMENT - Certified to CAN Standard</p>	<p>CAN/CSA-C22.2 No. 61010-1-12 UL Std. No. 61010-1 (3rd Edition)</p>
<p>3A</p> 	<p>3-A Certificate authorization number: 3500</p>	<p>Applied standard 3-A #46-03 Sanitary standard for refractometers and energy absorbing optical sensors for milk and milk products</p>

LLT100

Laser level transmitter

Dimensions

Dimensions in mm (in.)




Fig. 1: LLT100 with universal flange (aluminum and stainless steel)

Dimensions in mm (in.)




Fig. 2: LLT100 with class 150 flange

LLT100

Laser level transmitter

Dimensions in mm (in.)




Fig. 3: LLT100 with class 300 flange

LLT100

Laser level transmitter

Dimensions in mm (in.)






Fig. 5: LLT100 with triclover flange

Interface

HART terminal – 2 wires



HART terminal with heater option – 2 + 2 wires





LLT100

Laser level transmitter

Accessories


Dust tube

Dimensions in mm (in.)




Purge ring

Dimensions in mm (in.)



Dust tube assembly with purge ring




LLT100


Laser level transmitter

Cooling tube

Dimensions in mm (in.)




Cooling tube with universal flange



Cooling tube with high pressure flange


Adjustable pivot bracket

Dimensions in mm (in.)



Adjustable swivel flange

Dimensions in mm (in.)



LLT100

Laser level transmitter

Accessories — specifications

Dust tube

Base plate diameter

165 mm (6.5 in.) mounts on LLT standard flange

Length

257 mm (10.1 in.)

Material

316 Stainless steel

Gasket material

Black compressible Buna-N rubber durometer rating shore 60A

Function

Static air space prevents dust buildup, can be purged.
Offset from hot process interface to allow convection cooling, can be purged.

Flange reducer

Side A	2 in. ANSI class 150 raised face flange	DN50 PN40 raised face flange
---------------	---	------------------------------

Side B raised face	3 in. ANSI class 150	4 in. ANSI class 150	6 in. ANSI class 150	DN80 PN40	DN100 PN40	DN150 PN40
---------------------------	----------------------	----------------------	----------------------	-----------	------------	------------

Side B flat face	3 in. ANSI class 150	4 in. ANSI class 150	6 in. ANSI class 150	DN80 PN40	DN100 PN40	DN150 PN40
-------------------------	----------------------	----------------------	----------------------	-----------	------------	------------

Material 304 Stainless steel

Adjustable swivel flange

Outer diameter

210 mm (8.3 in.)

Mounting bolt pattern

3 bolt holes, 10 mm (0.4 in.) diameter

Tilt angle for aiming

Continuously adjustable from 0° to 6°

Material

Aluminum

Adjustable pivot bracket

Overall dimensions

185 x 249 55 mm (7.3 X 9.8 x 2.2 in.)

Opening diameter

60 mm (2.4 in.)

Mounting plate thickness

5 mm (0.2 in.)

Mounting bolt

4 x HHCS 5/8-11 X 2 SS, + 8 x Washers + 2 x lock washers + 4 x nuts, bolt hole 8 x 18 mm (0.7 in.)

Reflector

Function

Reflective panel for positioning applications up to 200 m (656 ft.)

Size

90 cm x 90 cm (36 in. x 36 in.)

Material

Aluminum with reflective paint

Cable glands

Description

Ex cable glands with ½ in. NPT or M20 thread size
Ex C1/D1 cable glands with ½ in. NPT or M20 thread size

Demo kit

Description

Rugged carrying case with LLT100, dust tube, battery pack, laser pointer tool

External laser pointer tool

Function

Laser pointer accessory used for targeting and aiming purpose.

Pointing laser

650 nm wavelength

Less than 1mW output power

Pointing laser safety

Class 2M

Ordering information

Base model	LLT100	.XX	.X	.X	.X	.XX		.XXX	.XXX
Body and electrical connection									
Aluminum body – M20 x 1.5		AM							
Stainless steel body – M20 x 1.5		SM							
Aluminum body – 1/2 in. NPT		AI							
Stainless steel body – 1/2 in. NPT and electrical connection		SI							
Demo kit		DEMO							
Process flange									
ASME 2 in. class 150/DIN 50mm PN16 bolt pattern, flat face, alu. cem. window			A						
ASME 2 in. class 150/DIN 50mm PN16 bolt pattern, flat face, SS, cem. window			B						
ASME 2 in. class 150, SS, raised face, fused window			C						
ASME 2 in. class 300, SS, raised face, fused window			D						
DIN 50mm PN16, SS, raised face, fused window			F						
DIN 50mm PN40, SS, raised face, fused window			G						
Triclover 4 in., SS, cem. window			H						
Heated window									
No heated lens				N					
With heated lens – requires 24 V input				H					
Communication protocol									
4 to 20 mA HART						10			
Display									
None – (blind cover)							L0		
Digital LCD integral display with TTG (Through-The-Glass) activated keypad							L5		
Additional order codes									
Explosion Protection Certifications (multi-choice)									
None									
ATEX (Ex d Cat 1/2G and 2D)								E01	
IECEX (Ex d Cat 1/2G and 2D)								E02	
ATEX (Ex d Cat 2G and 2D)								E05	
IECEX (Ex d Cat 2G and 2D)								E06	
FMus (Ex d CI, CII, CIII D1) Groups ABCDEFG								E03	
cFM (Ex d CI, CII, CIII D1) Groups BCDEFG								E04	
Cable glands and plugs									
ATEX/IECEX C1/D1 Cable gland NPT-1/2 and stopping plug									G01
ATEX/IECEX C1/D1 Cable gland M20 and stopping plug									G02
ATEX/IECEX Cable gland NPT-1/2 and stopping plug									G03
ATEX/IECEX Cable gland M20 and stopping plug									G04

LLT100

Laser level transmitter

	.XXXX	.XXXX	.XXXX	.XXXX	.XXXX	.XXX	.XXXX
Accessory options – tube (multi-choice)							
Dust tube	P901						
Cooling tube, no window, no pressure rating	P920						
Cooling tube, with window, no pressure rating	P921						
Cooling tube, process interface NPS 2 in. class 150 flange with window	P922						
Cooling tube, process interface NPS 2 in. class 300 flange with window	P923						
Cooling tube, process interface DN 50 PN40 flange with window	P924						
Accessory options – bracket							
Rotating bracket		A900					
Swivel flange		A910					
Accessory options							
Purge ring for dust tube			P910				
Dry-contact relay (4 to 20 mA HART) (qty 2)			DCMA				
Laser alignment tool			LAS				
Adaptor to LM80 bolt pattern			ADA				
Gaskets and o-rings							
Gasket (qty 2) for flat face process flange (A or B) BUNA-N				G900			
Triclover o-ring (qty 10), 4 in. diameter				G901			

continued

Accessory options – tube (multi-choice)	.XXXX	.XXXX	.XXXX	.XXXX	.XXXX	.XXX	.XXXX
Process flange converter							
Stainless steel 3 in./DN80 adaptor plate, class 150 and DN80/PN6 bolt pattern, non-pressure rated						PC03	
Stainless steel 4 in./DN100 adaptor plate, class 150 and DN100/PN10 bolt pattern, non-pressure rated						PC04	
Stainless steel 6 in./DN150 adaptor plate, class 150 and DN150/PN10 bolt pattern, non-pressure rated						PC06	
3 in. flat face ANSI class 150 flange converter						FC01	
4 in. flat face ANSI class 150 flange converter						FC02	
6 in. flat face ANSI class 150 flange converter						FC03	
3 in. raised face ANSI class 150 flange converter						FC04	
4 in. raised face ANSI class 150 flange converter						FC05	
6 in. raised face ANSI class 150 flange converter						FC06	
DIN80 flat face PN10 flange converter						FC07	
DIN100 flat face PN10 flange converter						FC08	
DIN150 flat face PN10 flange converter						FC09	
DIN80 raised face PN10 flange converter						FC10	
DIN100 raised face PN10 flange converter						FC11	
DIN150 raised face PN10 flange converter						FC12	
Certificate							
Material traceability certification						MTC	
Certificate of origin						COO	
Attested certificate of origin						ACO	
Calibration certificate						CC	
ID tag plate							
Supplemental wired-on stainless steel plate							WSSP
Supplemental screwed-on stainless steel plate							SSSP

Contact us

ABB Inc.

Process Automation
Level Measurement Products
3400, Rue Pierre-Ardouin
Québec (Québec) G1P 0B2
Canada

Tel.: +1 800 858-3847 (North America)
Tel.: +1 418 877-2944 (other countries)
Fax: +1 418 877-2834
Mail: Lasers@ca.abb.com

ABB Channel partner :

Intercontrol Meet- en Regeltechniek BV
IJsselburcht 26
6825 BP ARNHEM
The Netherlands

www.intercontrol.eu
info@intercontrol.eu
+31 (0) 26 442 5204



Note

We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB does not accept any responsibility whatsoever for potential errors or possible lack of information in this document.

We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction, disclosure to third parties or utilization of its contents - in whole or in parts - is forbidden without prior written consent of ABB.

Copyright© 2016 ABB
All rights reserved



Sales



Service