



# HVT 400-DP

## Failsafe Busbar Symmetry Monitor for +/- 1000 V



### Application

Monitoring the busbar symmetry is a safety-relevant task for different processes. For instance, in hydrogen electrolysis it is crucial for optimizing the efficiency, safety, and reliability of the process, as well as for ensuring consistent and high-quality hydrogen production.

Also, the device is used in battery test benches for electric vehicles. The two measurement inputs enable the comparison of input voltages and thorough self-monitoring ensures reliable detection of a fault condition. Freely configurable, fail-safe limit values are available for control system. Due to the flexible software configuration, the HVT 400 series is suitable for numerous industries and various applications.

### Scope of use

Battery Testing  
High power supplies  
Chlorine Alkaline Electrolysis

### Safety Features

Featuring a safety-by-design approach, the HVT 400-DP provides a wide range of diagnostic functions. In order to create a safety loop, the desired output must be evaluated in conjunction with one of the two diagnostic relays REL3/REL4. This way, two individually configurable safety outputs can be created, for which either the relays REL1/REL2 or the 4...20mA analog output are available.

## Main Benefits

- Failsafe voltage monitoring
- Simple software configuration via USB or Modbus
- 0-1500V measurement range (DC and true RMS AC versions are available)
- Redundant architecture
- Robust design with high dielectric strength
- SIL2 according to IEC/EN 61508
- Two individual safety outputs
- LED status: Power, Error, Alarm
- 10-year proof test interval

Technical Data	
Certificate	SIL 2 according to IEC 61508
Measurement range	0.. 1500V AC or DC
Input Resistance	12 MΩ
Analog Output Load	0/4 ... 20 mA
Accuracy	Max 500 Ω at 22mA < 0,5%
Contact outputs	Normally Open
Switching Power	Max 62,5 VA / Max 30W
Switching Voltage	Max 125VAC/110VDC
Switching Current	Max. 1A
Contact Material	AG Pd + 10 μAu
Status LEDs	Power: Green Error / SIL Alarm: Red REL1/REL2: Yellow
USB Interface	USB 2.0
RS485 Interface	Half duplex, no scheduling
Baud rate	9600 bps
Device Address	1-248
Supply	24VDC (20...30VDC)
Power Consumption	Max. 1,9W
Temperature Storage / Transport	-10°C...+60°C
Perm. Humidity	-20°C...+70°C
Max. operating Altitude	10%...90% r.H no cond. <2000m above mean sea level
Temperature Coefficient	<0,01%/K (max) <0,005%/K (typical)
Galvanic isolation	4,3 kV AC test voltage
Overvoltage category	CAT II: 1500V Pollution Degree 1
PCB Material	FR4
Housing Material	Polyamide
Protection Class	IP20
Flammability	V0
Mounting type	35mm DIN rail

Safety Properties	FMEDA
Category	SIL 2
Device type	Type B
HFT	0
SFF	95 %
DC	89 %
Safe failure rate	331 FIT
Safe detected failure rate	0 FIT
Safe undetected failure rate	331 FIT
Dangerous failure rate	362 FIT
Dangerous detected failure rate	325 FIT
Dangerous undetected failure rate	37 FIT

